# SB156SL-1-E

## SL STAPLER CT 40MM MAX

Diameter: 0.9 - 1.3mm
Crown: 8 - 8mm
Length: 12 - 40mm

## Features

- Aluminium Housing
- Rubber Comfort Grip
- No-Mar-Tip
- Dial-A-Depth
- Adjustable Exhaust
- Contact Trip
- Oil Free Engine
- Rear Exhaust
- Rear Loading

| SPECIFICATION | | | | | |
|---|---|---|---|---|---|
| Weight | 1.75 kg | | Operating pressure | | 4.80 - 7.00 BAR |
| Width | 76 mm | | | | 70.00 - 100.00 PSI |
| Length | 270 mm | | Air Consumption Ltr.per shot @ 5.6 bar | | 0.9 |
| Height | 275 mm | | Noise | **LPA 1sd** | 75.20 |
| Magazine capacity (max) | 110 | | | **LWA 1sd** | 82.60 |
| SL Series Fasteners: | | | | **LPA 1s, 1m** | 69.60 |
| Diameter (mm) | 0.9 (min) | 1.3 (max) | Vibration / Uncertainty | | 3.77 / 1.885 m/s2 |
| Crown (mm) | 8 (min) | 8 (max) | | | |
| Length (mm) | 12 (min) | 40 (max) | | | |