SL1838BC-E

BOSTITCH CAP STAPLER KIT

SL

Diameter: 0.9 - 1.3mm
Crown: 8 - 8mm
Length: 19 - 38mm

SB-CAPS

Diameter: 25 - 25mm
Crown: 25 - 25mm

Features

Mg Magnesium Housing

Rubber Comfort Grip

Anti Slip Bumpers

Oil Free Engine

Rear Exhaust

SPECIFICATION		
Weight	1.77 kg	
Width	159 mm	
Length	286 mm	
Height	267 mm	
Magazine capacity (max)	100	
SL Series Fasteners:		
Diameter (mm)	0.9 (min)	1.3 (max)
Crown (mm)	8 (min)	8 (max)
Length (mm)	19 (min)	38 (max)
SB-CAPS Series Fasteners:		
Diameter (mm)	25 (min)	25 (max)
Crown (mm)	25 (min)	25 (max)

Operating pressure		4.80 - 8.30 BAR
		70.00 - 120.00 PSI
Air Consumption Ltr.per shot @ 5.6 bar		1.33
Noise	**LPA 1sd**	86.59
	LWA 1sd	94.16
	LPA 1s, 1m	81.20
Vibration / Uncertainty		2.944 / 1.472 m/s2